

## RARALKYD SO-5605 XL

### FEATURES

High scratching and hardness  
Good for PU high gloss system as well as matt finish  
Can be used in PU sealers for high clarity finish

### APPLICATION

Mainly used for 2-pack polyurethane coatings for wood finishes  
Can be blended with short oil fast dry for PU sealer to enhance the sanding and drying properties  
Excellent for PU matt and glossy finish with high scratch proof

### CHARACTERISTICS

Oil Length	39.5%
Clarity	Clear
Solvent	Xylene
Oil Type	SOFA/HCO
Solid Content (% by wt)	60 +/- 1%
Viscosity (Gardner Scale@25°C)	Y - Z1
Acid Value	<15 mg KOH/g
OH Value (on solids)	3.6 - 3.8 mg KOH/g
Color (Gardner)	4 max

### SOLUBILITY DATA

Aromatic - Esters	Soluble
Aliphatic	Insoluble
Miniral Spirits	Limited
Ketones	Soluble
Alcohols	Limited

### DELIVERY FORM DETAILS

Supplied as 60% in Xylene packed in mild steel drums (Net. weight 200KG)

### SHELF LIFE

Minimum 12 months when stored under standard storage conditions

**DISCLAIMER:**

The information contained in this datasheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about the product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.