

## RARESTER SP-1603 XL

### FEATURES

Excellent drying with Isocyanates  
Excellent clear surface  
High sealer quality

### APPLICATION

PU sealers and high matt finish topcoats  
Matt PU coatings  
High sealer quality

### CHARACTERISTICS

Solvent	Xylene
Solids	60 +/- 1%
Hydroxyl value on solid	115 +/- 5
Oil length	33 +/- 1
Viscosity (Gardner scale @ 25°C)	Y - Z
Acid value	14- 17
Color (Gardner)	3 max
Clarity	Clear

### SOLUBILITY DATA

Aliphatic Solvents	Limited
Aromatic Solvents	Soluble
Ketones	Soluble
Esters	Soluble

### COMPATIBILITY DATA

Medium oil alkyd	Compatible
Long oil alkyd	Compatible
Rosin maleate	Compatible

### DELIVERY FORM DETAILS

Supplied at 60% in Xylene packed in Mild steel drums (Net. weight 200kg)

### SHELF LIFE

Minimum 12 months when stored under standard storage conditions

#### DISCLAIMER:

The information contained in this datasheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about the product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.

11th Floor, 1 Lake Plaza, Jumeirah Lake Towers, P.O. Box: 47381, Dubai UAE | Tel: +971 4 4356517, +971 4 4356516 | Fax: +971 4 4356518, Email: info@rarresin.com

WWW.RARRESIN.COM