

RARALKYD LO-17030 WS

FEATURES

- Very Good Gloss & Gloss retention
- Very Good adhesion & medium Hardness
- · Economically dark color paints
- Very good color retention

APPLICATIONS

- Interior & exterior decorative paints
- High viscosity paints
- Varnish floor sealers
- Very High gloss enamel

CHARACTERISTICS

• Oil %
Phthalic anhydride %
Solvent
• Oil type
Solid Content 70
• Viscosity Gardner @25°C @70% WS
• Viscosity Gardner @25°C @55% WS
• Viscosity CP @25°C @55% WS
 Acid Value mg KOH/gm solid
Color Gardner

SOLUBILITY DATA

Aliphatic hydrocarbon Aromatic Chlorinated Alcohols Esters Ketons **Glycol-Ethers**

29% White Spirit Soya bean oil 1% Approx. Z8 YΖ Approx. 2200 12 max 5 max

Soluble

Soluble

Soluble

Limited

Soluble Soluble

Soluble

58%

DISCLAIMER

The information contained in this datasheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about the product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.

11th Floor, 1 Lake Plaza, Jumeirah Lake Towers, P.O. Box: 47381, Dubai UAE | Tel: +971 4 4356517, +971 4 4356516 | Fax: +971 4 4356518, Email: info@rarresin.com WWW.RARRESIN.COM



COMPATIBILITY DATA

Medium oil Alkyd Short oil Alkyd Rosin maleate Zinc White Red Lead NC Chlorinated rubber Compatible Incompatible Compatible Compatible Incompatible Compatible

COMPATIBILITY DATA

Stand Oil Isocyanate Urea/melamine resins Compatible Incompatible Incompatible

DELIVERY FORM DETAILS

It's available at 70% in White Spirit

STORAGE CONDITIONS

RARALKYD LO-17030 WS Should be stored indoors in the original, unopednd and undamaged containers in a dry place at storage temperatures between 5°C & 30°C Exposure to sun shine should be avoided.

SHELF LIFE

Under the above mentioned storage conditions the satability of RARALKYD LO-17030 WS will be 12 months ex-work

DISCLAIMER:

The information contained in this datasheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about the product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.

11th Floor, 1 Lake Plaza, Jumeirah Lake Towers, P.O. Box: 47381, Dubai UAE | Tel: +971 4 4356517, +971 4 4356516 | Fax: +971 4 4356518, Email: info@rarresin.com W W W. R A R R E S I N. C O M