

RARALKYD LO-1555 WS

FEATURES

Fast drying
Good Gloss
Good Hardness

APPLICATION

Decorative enamels

CHARACTERISTICS

Oil Length	52 %
Solvent	White Spirit
Oil type	Soya
Solid Content (% by wt)	55+/-1%
Viscosity (Gardner scale @25 C)	U – V
Acid Value on solids(mg KOH/g)	< 15
Color (Gardner 1933)	5 max

SOLUBILITY DATA

Aromatic Hydrocarbons	Soluble
White Spirits	Soluble
Alcohols	Soluble
Esters	Soluble
Ketones	Soluble

COMPATIBILITY DATA

Medium oil Alkyds	Compatible
Short Oil Alkyds	Incompatible

DELIVERY FORM DETAILS

Mild steel drums (Net .Weight 190 Kg)

SHELF LIFE

Minimum 12 months in original unopened containers stored between 5 and 35 C

DISCLAIMER:

The information contained in this datasheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about the product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.

11th Floor, 1 Lake Plaza, Jumeirah Lake Towers, P.O. Box: 47381, Dubai UAE | Tel: +971 4 4356517, +971 4 4356516 | Fax: +971 4 4356518, Email: info@rarresin.com

WWW.RARRESIN.COM