

# **RARALKYD LO-1558 WS**

#### FEATURES

Fast drying Good Gloss Good Hardness

## APPLICATION

Decorative enamels

### CHARACTERISTICS

Oil Length Solvent Oil type Solid Content ( % by wt) Viscosity (Gardner scale @25 C) Acid Value on solids(mg KOH/g) Color (Gardner 1933)

### SOLUBILITY DATA

Aromatic Hydrocarbons	
White Spirits	
Alcohols	
Esters	
Ketones	

#### COMPATIBILITY DATA

Medium oil Alkyds Short Oil Alkyds Compatible Incompatible

5 %

Soya

U – Z

5 - 10

4 max

Soluble Soluble Soluble Soluble Soluble

55+/-1%

White Spirit

# **DELIVERY FORM DETAILS**

Mild steel drums (Net .Weight 190 Kg)

#### SHELF LIFE

Minimum 12 months in original unopened containers stored between 5 and 35 C

DISCLAIMER:

The information contained in this datasheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about the product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.

11th Floor, 1 Lake Plaza, Jumeirah Lake Towers, P.O. Box: 47381, Dubai UAE | Tel: +971 4 4356517, +971 4 4356516 | Fax: +971 4 4356518, Email: info@rarresin.com WWW.RARRESIN.COM