

RARCYNAN 5052

FEATURES

Fast drying & hardness compatibility with polyol

PHYSICAL CHARACTERISTICS

Wood
Polyurethane varnish
Silk screen ink
Primer
Stamping foil
Synthetic leather

CHARACTERISTICS

| | |
|-------------------------|-----------|
| White Spirit | Insoluble |
| Xylene | Insoluble |
| Toluene | Insoluble |
| Insoluble Butyl Acetate | Complete |
| Ethyl Acetate | Complete |
| MEK | Complete |

COMPATIBILITY DATA

| | |
|----------------------------|------------|
| Alkyd Polyol | Compatible |
| Acrylic Polyol | Compatible |
| Polyester Polyol | Compatible |
| Cellulose Acetate Butylate | Compatible |
| Nitrocellulose | Compatible |

Packing: 210 Kgs net mild steel drums.

Storage: The resin is sensitive to moisture and should be stored indoors in the original unopened and undamaged containers in a dry place at storage temperatures 5 & 25 Exposure to direct sunlight should be avoided.

Shelf Life: Minimum 6 months when stored under the above ambient storage conditions

DISCLAIMER:

The information contained in this datasheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about the product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.

11th Floor, 1 Lake Plaza, Jumeirah Lake Towers, P.O. Box: 47381, Dubai UAE | Tel: +971 4 4356517, +971 4 4356516 | Fax: +971 4 4356518, Email: info@rarresin.com

WWW.RARRESIN.COM