

# RARCYAN 75L

## 1 IDENTIFICATION OF THE PRODUCT AND THE COMPANY

### 1.1 IDENTIFICATION OF THE SUBSTANCE:

IDENTITY (As used on label and list) : RARCYAN 75L

### 1.2 IDENTIFICATION OF THE COMPANY:

RAR Resin & Chemical Industries JLT  
11th Floor, Jumeirah Lake Towers, P.O. Box: 47381, Dubai UAE  
Tel: +971 4 4356516 / +971 4 4356517 Email: info@rarresin.com  
Fax: +971 4 4356518 Website: www.rarresin.com

## 2 COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)	CAS NO.
Isocyanate Prepolymer	N/Av	N/Av	N/Av	75%	
Ethyl Acetate	N/Av	N/Av	N/Av	25%	141-78-6

## 3 PHYSICAL/ CHEMICAL CHARACTERISTICS

**Boiling Point** : 77.1 deg C (Ethyl acetate)  
**Specific Gravity (H<sub>2</sub>O= 1)** : 1.08  
**Vapor Pressure (mm Hg)** : unknown  
**Melting point** : N/Av  
**Vapor Density (AIR = 1)** : unknown  
**Evaporation Rate** : -  
**Solubility in Water** : Insoluble  
**Appearance and Odor** : Clear, pale yellow liquid with characteristic odor

## 4 FIRE FIGHTING MEASURES

**Extinguishing Media** : Dry Chemical, foam, water spray and CO<sub>2</sub>  
**Special Fire Fighting Procedures** : Liberation of Nitrous fumes by Thermal decomposition or combustion  
**Unusual Fire and Explosion Hazards** : When exposed to direct heat source, combustible vapor will generate, which can explode when mixed with air and ignited

## 5 MEASURES IN CASE OF ACCIDENTS

**Spillage / Leakage** : Do not empty into drains. remove mechanically cover remainders with wet, absorbent material (chemical binder based on calcium silicate hydrate, sand) After approx. one hour transfer to waste container and do not seal. Keep damp in a safe ventilated area for several days.

### DISCLAIMER

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.

## 6 HANDLING AND STORAGE

**Handling:** The operator should be trained in handling this product. When the drum is pressurized, unscrew the bung slowly to release the pressure before taking it off.  
This product should not be filled in as unwashed or wet container.  
The use of fire is strictly prohibited in the working area.  
Those who show allergenic and sensitizing effects should not be in charge.

**STORAGE:** Keep container properly sealed and stored indoors in a well ventilated area.  
Once opened, the container should be closed and sealed with nitrogen gas.  
If stored outdoors, the container should be covered with waterproof canvas sheet to avoid being exposed in the rain.

## 7 HAZARDS IDENTIFICATION

**Health:** The risk of concentration- dependent irritating effects on eyes, nose, throat and perspiratory.  
**Physical:** The product reacted with water forming CO<sub>2</sub> so container may rupture or explode  
**Eye contact:** Irritation, blurred vision, damage  
**Ingestion:** Vomiting, diarrhea, stomach pain, irregular heartbeat  
**Skin contact:** Allergic reactions, skin disorders, rash  
**Inhalation:** Depress central nervous system and results in stupor

## 8 FIRST AID MEASURE

In case of eye contact rinse carefully and thoroughly with water and seek medical advice. In case of skin contact wipe off mechanical and wash afflicted areas thoroughly with soap and plenty of water. In case of irritation of the respiration tract or swallowing, consult a doctor.

## 9 CONTROLS/ PERSONAL PROTECTION

**Technical protection :** Keep container dry and tightly closed in a cool and well ventilated place.  
Avoide exposure to temperature above 50°C. Ensure adequate ventilation or exhaust ventilation in the working area.

**Personal Protection :** Wer suitable protective clothing, protective gloves, goggles/ mask

## 10 CHEMICAL REACTIVITY/ STABILITY

**Chemical stability:** Good stable (Avoid to high temperature and moisture)  
**Incompatibility :** This product react with active hydrogen groups such as amines and alcohols  
**Decompostion :** Reaction with water produces heat and carbon dioxide gas.  
**Polymerization :** Polymerization by alkaline materials and amines.

## 11 INFORMATION ON TOXICITY

**Acute toxicity :** LD 50 oral : NO DATA  
LC 50 inhalation: NO DATA

### Subacute inhalation toxicity :

**Chronic toxicity:** Prolonged to the vapor or mist may reduce the function of the lungs.  
Sensitizing effect on the skin may be chronic

**Carcinogenic effect :** No data on the effect on human beings ( the IARC test)

### DISCLAIMER

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.

**Mutagenic effect:** No Data.  
**Irritation :** Prolonged contact on the skin and eye will cause reddish swelling or severe pain

## 12 ECOLOGICAL INFORMATION

**Biodegradability** : Not available  
**Bioaccumulation** : Not available  
**Fish toxicity** : Not available  
**Other information on ecotoxicity** : Not available

## 13 DISPOSAL CONSIDERATIONS:

**Disposal methods** : Incinerate in an appropriate facility  
Treat by authorized agents professionally trained in disposing  
**Industrial waste** : Dispose after forming solid form through reaction with polyol  
**Handling** : Empty drum should be left to stand with water and left to stand for 48 hours.  
Water should subsequently be removed afterward

## 14 TRANSPORT INFORMATION

GGVSee / IMDG Code : - -	UN NO : - -	MFAG : - - EMS : - -
GGVE / GGVS : Class - - No. - -		RID / ADR : Class - - No. - -
ADNR : Class - - No. - -	Cat - -	ICAO / IATA - DGR : NOT RESTR

**Following all the regulations in your country**

**Perform under the supervision of an authorized operator**

**Other information** Not dangerous cargo  
Keep dry  
Keep separated from foodstuffs

## 15 REGULATORY INFORMATION

Following all the regulations in your country

## 16 OTHER INFORMATION

Reason for issue : Update to new format  
Prepared : RAR Resin Technical Dept.