

XYLENE

Test Description	Specification Limits		Unit of Measure	ASTM Test Method
	Min.	Max.		
Appearance	Clear			Visual
Purity as Aromatic	99.9		Vol. %	ASTM D 1319
Saybolt Colour	+30			ASTM D 156
Density at 15deg.C			Kg/dm3	ASTM D 4052
Distillation Range			Deg.C	ASTM D 850
IBP	137.8			
50%	139.6			
DP	142.6			
Flash Point	27.5		Deg.C	ASTM D 56
Aniline Point	Not Listed		Deg.C	ASTM D 611
Copper Corrosion 3hrs. at 50 deg.c	1a			ASTM D 130
Sulphur Content	Free		ppm/wt	ASTM D853
Aromatics	99.9		Vol.%	ASTM D 1319
Hydrogen Sulphide	Free		ppm/wt	ASTM D 853

DISCLAIMER:
The information contained in this datasheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about the product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.