

## METHANOL

Test	Unit	Method	Specification
Appearance		IMPCA 003-98	Clear & free of Suspended Matter
Purity on Dry Basis	%wt.	IMPCA 001-02	Min 99.85
Acetone content	Mg/kg	IMPCA 001-02	Max 30
Ethanol	Mg/kg	IMPCA 001-02	Max 50
Color Pt-Co	Pt-Co	ASTM D 1209	Max 5
Water	%wt.	ASTM E 1064	Max 0.1
Distillation at 760mm Hg	.....	.....	.....
Initial Boiling Point	°C	ASTM D 1078	Max Range 1.0°C
Dry Point	°C	ASTM D 1078	Including 64.6=0.1°C
Range	°C	.....	0.1°C
Specific Gravity @ 20°/20°	.....	ASTM D 4052	0.791-0.793
PTT at 15°C	Minutes	ASTM D 1363	Min 60
Chloride as C1	Mg/kg	IMPCA 002-08	Max 0.5
Hydrocarbons	Visual	ASTM D 1722	Pass test
Carbon sable Substances	Pt-Co	ASTM E 346	Max 30
Acidity as Acetic Acid	Mg/kg	ASTM D 1613	Max 30
Total Iron	Mg/kg	ASTM E 393	Max 0.1
Non Volatile Matter	Mg/1000ml	ASTM D 1353	Max 8
Odor	.....	ASTM D 1296	*

\* Characteristic & Non-Residual Odour

**DISCLAIMER**

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.