

Butanol (Technical Grade)

**PRODUCT CODE
DESCRIPTION**

2051
C₄/C₅ alcohol distillation cut.

Properties	Units	Limits	Test Methods
Appearance		Clear and bright	ASTM E2680
Colour	Pt-Co	5 max	ASTM D1209; ASTM D5386
Water	mass %	0.10 max	ASTM D1364
n-Butanol	mass %	60.0 min	GC
sec-Pentanol	mass %	20.0 max	GC
Total alcohols	mass %	99 min	GC
Carbonyls as propionaldehyde	mass %	0.30 max	B124

Further Properties	Units	Typical values	Test Methods
Density at 20°C	g/ml	0.808-0.811	ASTM D4052
Iso-butanol	mass %	12	GC
Distillation at 101.3 kPa: Initial boiling point Dry point	°C °C	115 118	ASTM D1078

The sales Specification values are continuously checked, documented and stored within the scope of quality assurance.

Further properties are of an informational nature only and are not checked regularly. If the Sales Specifications are complied with, it can generally be assumed that all further properties and typical data conform to the values given.

DISCLAIMER:

The information contained in this datasheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about the product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.