

## METHYL ACETATE

### Description:

**CAS No.** :79-20-9  
**Molecular Mass** :90.14

### Applications:

**Paints:** It is used as solvent to manufacture fast drying paints for wood finishing, automobile, industrial application, and marine applications.

**Surface cleaner:** It is used as solvent in surface cleaner because it is fast drying and hydrophobic in nature so it does not attract water and dust during cleaning of surface.

**Adhesives:** It is used to manufacture fast sticking adhesives, which is manufactured by mixing rubber and resins in methyl acetate.

**Other application:** It is also used to manufacture cosmetics and personal care products like nail polish, nail polish remover, perfumes

### Speciation:

Appearance	Colorless liquid
Purity	80% "Min."
Methanol	20% "Max."
Specific Gravity @ 20 °C	>0.898
Water	0.2%

### Packing:

180 Kgs/Steel drums, 205Kgs/HDBE drums, ISO Tank 20,000 Kgs

**DISCLAIMER:**

The information contained in this datasheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about the product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.