

BUTYL GLYCOL ETHER

Product Specification - Version 4a

Specification	Minimum	Maximum	Test Method
Purity (wt%)	99.0		GC
Water (wt%)		0.1	ASTM D1364
Acid Number (mgKOH/g)		0.05	ASTM D974
Color (Pt-Co)		10	ASTM D1209
Appearance	Clear and free		ASTM D4176
Further Properties:			
Density @20C (g/ml)	0.899	0.901	ASTM D4052
Refractive Index (nD20)	1.419	1.420	ASTM D1218
Distillation range @ 101.3 kPa (degrees C)			ASTM D1078
Initial Boiling Point	168		
Dry Point		172	

DISCLAIMER:
The information contained in this datasheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about the product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.

11th Floor, 1 Lake Plaza, Jumeirah Lake Towers, P.O. Box: 47381, Dubai UAE | Tel: +971 4 4356517, +971 4 4356516 | Fax: +971 4 4356518, Email: info@rarresin.com

WWW.RARRESIN.COM