MATERIAL SAFETY DATA SHEET



n-Propanol Technical

1. Chemical product and company identification

Trade name : n- Propanol Technical

Synonym: n- Propanol, 1- propanol, hydroxypropane, 1-propyl alcohol,

Ethyl carbinol, n-propan-1-ol, Propylic acid, n-Propyl alcohol

Product code : 2044

Use : Solvent, for industrial use only

Manufacturer / Supplier / Distributor Information

RAR Resin & Chemical Industries JLT

11th Floor, Jumeirah Lake Towers, P.O. Box: 47381, Dubai UAE

2. HAZARDS IDENTIFICATION

Identification of the risk

R11 : Highly Flammable

R41 : Risk of serious damage to eyes.

R67 : Vapours may cause drowsiness and dizziness.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Propan-1-ol; n-propanol

Contents : 99.90 % W/W

CAS-No : 71-23-38 Index-No. :603-003-00-0 EC-No. : 200-746-9

Symbol(s): F, Xn R-phrase(s) -R11-R41-R67

For the full text of the R-phrase mentioned in this Section, see Section 16

4. FIRST AID MEASURES

General advice : When symptoms persist or in all cases of doubt seek medical

advice

Inhalation : Move to fresh air in case of accidental inhalation of vapours. If

breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

Skin contact: Wash off immediately with soap and plenty of water while removing

all contaminated clothes and shoes. Wash contaminated clothing

before re-use. If skin irritation persists, call a physician.

DISCLAIMER

Eve contact : Rinse thoroughly with plenty of water for at least 15 minutes and

consult a physicial

Ingestion : if swallowed, seek medical advice immediately and show this

container or label. Do not induce vomiting without medical advice.

Never give anything by mouth to an unconscious person.

5. FIREFIGHTING MEASURES

Suitable extinguisghing media : Water spray, Alcohol-resistant foam, Dry chemical, Carbon dioxide

(CO₂)

Extinguishing media which shall not be used for safety reasons

: No information available.

Specific hazards during

firefighting

: Flash back possible over considerable distance

Special protective

equipement for firefighters

: Wear self-contained breathing apparatus and protective suit.

Further infomation : Cool containers/ tanks with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Keep people away from and upwind of spill/ leak. Remove all

sources of ignition. Do not breathe vapours or spray mist.

Environmental precautions

: Should not be released into the environment. Prevent further

leakage or spillage if safe to do so.

Methods for cleaning up : Soak up with inert absorbent material and dispose of as

hazardous waste.

7. HANDLING AND STORAGE

Handling

Safe handling advice : Provide sufficient air exhange and/or exhaust in work rooms.

> Wear personal protective equipment. Take precautionary measures against static discharge. Ensure all equipements is electrically

grounded before beginning transfer operations.

Advice on protection against fire and explosion : Keep away from heat and sources of ignition. Use explosion- proof

equipment.

Storage

Requirements for storage areas and containers

: Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Components with workplace control parameter

NATIONAL OCCUPATIONAL EXPOSURE LIMITS

Contains no substances with occupational exposure limit values.

EUROPEAN OCCUPATIONAL EXPOSURE LIMITS

Contains no substances with occupational exposure limit values

Engineering measures

Provide sufficient air exchange and/ or exhaust in work rooms.

Personal protective equipment

Respiratory protection : In case of sufficient ventilation, wear suitable respiratory

equipment.

Hand protection : Gloves suitable for permanent contact:

Material: butyl-rubberBreak through time: 4 hMaterial thickness: 0.5 mm

Eye protection : Safety glasses with side- shields

Skin and body protection : Protective suit, Safety shoes

Hygiene measures : Wash hands before breaks and immediately after handling

the product.

Protective measures : Wear suitable protective equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : Liquid

State of matter : Liquid; at 20 °C; 1,013 hPa

Colour: ColourlessOdour: Alcohol- like

pH : 7

Melting point/range : -126.3 °C Boiling point/ boiling : 97.2 °C

range

Flash point : 26 °C; Closed cup

DISCLAIMER

Flash point : 26 °C; Closed cup

Autoignition temperature: 371 °CLower explosion limit: 2.1 % (V)Upper explosion limit: 13.5 % (V)

 Vapour pressure
 : 27.998 hPa; 25 °C

 Density
 : 0.805 g/cm3

Water Solubility : Completely miscible

Viscosity, dynamic : 2.710 mPa.s

Relative vapour density : 2.1

10. STABILITY AND REACTIVITY

Materials to avoid : Strong oxidizing agents, Incompatible with acids,

halogenated compounds

Hazardous : Carbon oxides

decomposition products

Hazardous rections : hazardous polymerisation does not occur.

11. TOXICOLOGICAL INFORMARION

Acute oral toxicity: LD50 rat: 1,870 mg/kg; literature valueAcute inhalation toxicity: LC50 rat: 4,000 mg/l; 4 h; literature valueAcute dermal toxicity: LD50 rabbit: 4,060 mg/kg; literature

Skin irritation: May irritate skin.Eye irritation: Slight irritation.Sensitization: No data availableCarcinogenicity: No data available

Reproductive toxicity : This information is not available.

Human experience: If : harmful by inhalation

Inhaled

Human experience: In : No harmful information is available

case of skin contact

Human experience: In : Irritating to eyes.

case of eye contact

12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Toxicity to fish : LC50 Pimephales promelas: 4,480 mg/l; 96 h; literature

value

13. DISPOSAL CONSIDERATIONS

Product : In accordance with local and national regulations. Do not

contaminate ponds, waterways or ditches with chemical or used container, The product should not be allowed to enter

drains, water courses or the soil.

Contaminated packaging : Do not burn, or use a cutting torch on, the empty drum., triple

rinse containers., Can be offered for recycling, re- conditioning

or puncture

DISCLAIMER

14. TRANSPORT INFORMATION

ADR : UN number: 1274; Class 3; packaging group: III; F1; Description

of the goods: n-PROPANOL

RID : UN number: 1274; Class 3; packaging group: III; F1; Description

of the goods: n-PROPANOL

ADNR : UN number: 1274; Class 3; packaging group: III; F1; Description

of the goods: PROPHYL ALCOHOL, NORMAL

IMDG : UN number: 1274; Class 3; EmS: F-E, S-Dpackaging group: III;

F1; Description of the goods: n-PROPANOL

ICAO/ IATA : UN number: 1274; Class 3; packaging group: III; F1; Description

of the goods: n-PROPANOL

15. REGULATORY INFORMATION

Labelling





Regulatory base : 67/548/EEC

Symbol(s) : F: Highly flammable

Xi: Irritant

R-phrase(s) R11: Highly Flammable

R41: Risk of serious damage to eyes

R67: vapours may cause drowsiness and dizziness

S-phrase(s) S 7: keep container tightly closed

S 16: Keep away from sources og ignition- No smoking

S 24: Avoid contact with skin.

S 26: In case of contact with eyes, rinse immediately with plenty

of water and seek medical advice S 39: Water eye/ face protection.

DISCI AIMER