MATERIAL SAFETY DATA SHEET



LEAD OCTOATE 36%

1 IDENTIFICATION OF THE PRODUCT AND THE COMPANY

1.1 IDENTIFICATION OF THE SUBSTANCE / PREPARATION:

Product Name: LEAD OCTOATE 36% Applications: INK / PAINT DRIER

1.2 IDENTIFICATION OF THE COMPANY:

RAR Resin & Chemical Industries JLT

11th Floor, Jumeirah Lake Towers, P.O. Box: 47381, Dubai UAE

2 COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS

INGREDIENTS TOXICITY DATA LD_{so} / LC_{so} NA OR UN # C.A.S. #

LEAD OCTOATE LD_{so} Oral (RAT) -3900 Mg/Kg

(From Similar Type Material) UN 1263 301-08-6

MINERAL SPIRIT LD₅₀ Oral (RAT) -1000 Mg/Kg

Dermal (RAT) -1000 5000 Mg/Kg UN 1225 64475-85-0

3 HAZARDOUS INDENTIFICATION

HAZARDOUS TOXICITY DATA LD_{50} / LC_{50} NA OR UN # C.A.S. # INGREDIENTS

- · Harmful by inhalation and if swallowed
- · May cause sensitization by skin contact
- · Harmful May cause lung amage if swallowed
- · Repeated exposure may cause skin dryness or cracking

4 FIRST AID MEASURES

GENERAL Contaminated clothing should be removed and washed before being re-used.

Inhalation Remove victim immediately from source of exposure Move the exposed person to fresh air at once get

medical attention if any discomfort continues.

Ingestion DO NOT induce vomitiing Get medical attantion immediately Drink plenty of water

Wash the skin immediately with soap and water Remove and clean contaminated cloth and shoes get

Skin medical attention if any discomfort continues.

Promptly wash eyes with plenty of water. Hold eyelids apart to ensure washing of the entire surface of

Eyes the eyes and lids with water. Get Medical attention immediately Continue to rinse.

DISCI AIMER

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.

5 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA SPECIAL FIRE FIGHTING

PROCEDURES

Use Water spray fog or mist Foam, Carbon dioxide CO2 Sand dolomite etc.

Avoid Wated in straight hose stream will scatter and spread fire Cool containers exposed to flames with untill well after the fire is out Keep run-off water out of sewers and water

sources, Dike for water control.

UNUSUAL FIRE & EXPLOSION HAZARDS

PROTECTIVE MEASURES IN

CASE OF FIRE

Vapour-air mixture is explosive Keep containers cool by sraying water.

Wear self-contained breathing apparatus and full protective gear

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

PREACAUTIONS TO
PROTECT ENVIRONMENT

Use Water spray fog or mist Foam, Carbon dioxide CO2 Sand dolomite etc.

Avoid Wated in straight hose stream will scatter and spread fire Cool containers exposed to flames with untill well after the fire is out Keep run-off water out of sewers and water

sources, Dike for water

SPILL CLEAN-UP METHODS Extinguish all ignition sources. Avoid sparks, flames, head and smoking. Ventilate

absorb or earth and place into containers.

7 HANDLING AND STORAGE

HANDLING PRECAUTIONS Avoid spilling skin and eye contact. Keep away from heat sparks and open flame,

Ventilate well. Avoid breathing vapours. Use apprived respirator if air contaminated is

above accepted level.

STORAGE PRECAUTIONS

STORAGE CRITERIA

Keep in cool, dry, ventilated storage and closed containers

Chemical storage, Flammable liquid storage.

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

VENTILATION Provide adequate general and local exhaust ventilation.

RESPIRTORSNo specific recommendation mande but respiratory protection may still be required

under exceptional circumstances when excessive air contamination exists. In conditions where high concontration of vapours are present of exposure limits are exceeded. wear a respirator that has been selected by a technically qualified person for the specific work

conditions.

PROCTECTIVE GLOVES
EYE PROTECTION

OTHER PROTECTION

OTHER PROTECTION W

Chemical resistant gloves required for prolonged or repeated contact

Wear splash-proof, chemical safety goggles to prevent any possibility of eye contact.

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENIC WORK ROUTINES Change work cloth daily before leaving work place. Employees should wash their hand

and face before eating drinking. DO NOT SMOKE IN WORK AREA.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE / PHYSICAL Pale Yellow Liquid

STATE

COLOR Pale Yellow Liquid

% Non-volatile matter 70 - 80 %% Metal Content $36 \pm 0.5 \%$ Specific Gravity @ 25°C 1.3 - 1.4 %Flash Point 55° C

Solubility in water Insoluble

DISCLAIMEE

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.

10 STABILITY AND REACTIVITY

No particular stability concerns **STABILITY**

MATERIAL TO AVOID Strong oxidizing agents.

HAZARDOUS Combustion can produce oxides of carbon and compounds of the contained metal(S).

DECOMPOSITION

PRODUCTS

11 TOXICOLOGICAL INFORMATION

Concentrated solvent vapours may cause headache and in severe cases incoodination. **INHALATION**

Nausea, vomiting and abdominal pain INGESTION SKIN Prolonged contact may cause irritation

EYES May cause irritation

HEALTH WARNINGS Long term effects. On prolonged or repeated skin contact there is a risk dermatitis

12 ECOLOGICAL INFORMATION

ENVIRONMENTAL

HAZARDS Avoid washing onto water courses. Avoid contamination public draind or water supply.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS Dispose of in accordance with local national regulations. DO NOT cut. Burn or use flames

on or near drums.

14 TRANSPORT INFORMATION

Under 454 L - Via Land No special shipping requirements.

Over 454 L - Vial Land PAINT RELATED MATERIAL, Class 3, UN 1263 P.G.III, Labels required. Flammable/UN

1263

ANY QUANTITY - VIA SEA No special shipping requirements. PAINT RELATED MATERIAL, Class 3, UN 1263

P.G.III, flash Point 55°C Labels required. Flammable Liquid Class 3.

ANY QUANTITY - VIA SEA PAINT RELATED MATERIAL, Class 3, UN 1263 P.G.III, Flash Point 55°C Labels required.

Flammable Liquid Class 3.

15 REGULATORY INFORMATION

LABEL FOR SUPPLY:

RISK PHRASES R10 Flammable

> Harmful - may cause lung damage if swallowed. R65

SAFETY PHRASES Do not breathe vapours S23

> S24 Avoid contact with the skin S37 Wear suitable gloves

S46 If swallowed, seek medical advice immediately and show this container or

label.

GUIDANCE NOTES Users are advised to consult these regulations for further information

16 OTHER INFORMATION

The information contained herein is based on current knowledge and experience, no responsibility is accepted that the information is sufficient or correct in all cases. Users should consider these data as a supplements to other information gathered by them and must make independent determainations of suitability and completeness of information from all sources to assure proper use and disposal of these material and the safety and health of employees, customers and third parties and the protection of the environment.