

RARALKYD MO-1605 XL

FEATURES

High molecular weight fast drying and good outdoor durability Suggested for economic guick dry primer pigmented

APPLICATION

Good performance in industrial paints Good overocat characteristics

CHARACTERISTICS

Oil Length	46 %
Solids	60 +/- 1%
Solvent	Xylene
Oil type	SOFA
Color Gardner	4 max
Viscosity Gardner	>Z9
Acid Value on solids	15 max

SOLUBILITY DATA

Aliphatic solvents
Aromatic solvent
Ketones
Alcohols
Esters

Soluble Soluble Soluble Insoluble Soluble

COMPATIBILITY DATA

Medium Oil Alkyd Long oil Alkyds Rosin Oil Alkyds

Compatible Compatible Compatible

DELIVERY FORM DETAILS

60% in Xylene - drums (185kg/drum)

SHELF LIFE

Minimum 12 months when stored under standard storage conditions

DISCLAIMER

The information contained in this datasheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about the product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.

11th Floor, 1 Lake Plaza, Jumeirah Lake Towers, P.O. Box: 47381, Dubai UAE | Tel: +971 4 4356517, +971 4 4356516 | Fax: +971 4 4356518, Email: info@rarresin.com WWW.RARRESIN.COM