

# BUTYL ACRYLATE

## 1 IDENTIFICATION OF THE PRODUCT AND THE COMPANY

### 1.1 IDENTIFICATION OF THE SUBSTANCE / PREPARATION:

Product Name: Butyl Acrylate  
Catalog Codes: SLB1666  
CAS#: 141-32-2  
RTECS: UD3150000  
TSCA: TSCA 8(b) inventory: Butyl Acrylate  
CI#: Not available.  
Synonym: Acrylic acid n-butyl ester; Acrylic acid, butyl ester; Butyl-2-propenoate; n-Butyl acrylate  
Chemical Name: 2-Propenoic acid, butyl ester  
Chemical Formula: C7-H12-O2

### 1.2 IDENTIFICATION OF THE COMPANY:

RAR Resin & Chemical Industries JLT  
11th Floor, Jumeirah Lake Towers, P.O. Box: 47381, Dubai UAE  
Tel: +971 4 4356517 / +971 4 4356516 Email: info@rarresin.com  
Fax: +971 4 4356518 Website: www.rarresin.com

## 2 COMPOSITION / INFORMATION ON INGREDIENTS

### Compositon:

Name	CAS#	% by Weight
Butyl Acrylate	141-32-2	100

**Toxicological Data on Ingredients:** Butyl Acrylate: ORAL (LD50): Acute: 900 mg/kg [Rat]. 5880 mg/kg [Mouse]. DERMAL (LD50): Acute: 1780 mg/kg [Rabbit]. Vapor (LC50): Acute: 2730 ppm 4 hours [Rat]. 7800 mg/m 2 hours [Mouse].

## 3 HAZARDS IDENTIFICATION

### Potential Acute Health Effects:

Hazardous in case of skin contact (Permeator), of eye contact (irritant), of ingestion, of inhalation (lung irritant). Slightly hazardous in case of skin contact (irritant).

### Potential Chronic Health Effects:

CARCINOGENIC EFFECTS: 3 (Not classifiable for huma.)by IARC, MUTAGENIC EFFECTS: Not available. TERA-TOGENIC EFFECTS: Not available. DEVELOPMENT TOXICITY: Not available. The substance may be toxic to kidneys, lungs, liver, upper respiratory tract, skin, eyes. Repeated or prolonged exposure to the substance can produce target organs damage.

#### DISCLAIMER

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.

#### 4 FIRST AID MEASURES

**Eyes:** Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. WARM water MUST be used. Get medical attention.

**Skin Contact:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.

**Serious Skin Contact:** Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.

**Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**Serious Inhalation:** Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. WARNING: It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek medical attention.

**Ingestion:** Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

**Serious Ingestion:** Not available.

#### 5 FIRE AND EXPLOSION DATA

**Flammability of the Product:** Flammable.

**Auto-Ignition Temperature:** 279 C (534 F) - 292°C (557.6°F)

**Flash Point:** CLOSED CUP: 29°C (84.2°F) - 39 C (102.2F). OPEN CUP: 47.778°C (118°F).

**Flammable Limits:** LOWER: 1.3% - 1.7% UPPER: 9.4% - 9.9%

**Products of Combustion:** These products are carbon oxides (CO, CO<sub>2</sub>)

**Fire Hazards in Presence of Various Substances:** Highly flammable in presence of open flames and sparks, of heat . Non-flammable in presence of shocks.

**Explosion Hazards in Presence of Various Substances:** Risks of explosion of the product in presence of mechanical impact: Not available. Slightly explosive in presence of open flames and sparks.

**Fire Fighting Media and Instructions:** Flammable liquid, soluble or dispersed in water. SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use alcohol foam, water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.

**Special Remarks on Fire Hazards:** Vapor may travel considerable distance to source of ignition and flash back.

**Special Remarks on Explosion Hazards:** Vapors may form explosive mixtures with air.

#### 6 ACCIDENTAL RELEASE MEASURES

**Small Spill:** Absorb with an inert material and put the spilled material in an appropriate waste disposal.

**Large Spill:** Flammable liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed.

#### 7 HANDLING AND STORAGE

**Precautions:** Keep away heat. Keep away from sources of ignition. Keep away from direct sunlight or strong incandescent light. Ground all equipment containing material. Do not breathe gas/fumes/vapor/spray. Avoid shock and friction. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, acids, alkalis.

**Storage:** Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). Sensitive to light. Store in light-resistant containers.

#### DISCLAIMER

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.

## 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering Controls:** Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure the eyewash stations and safety showers are proximal to the work-station location.

**Personal Protection:** Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

**Personal Protection in Case of a Large Spill:** Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self contaminated breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

**Exposure Limits:** Not available.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

**Physical State and appearance:** Liquid

**Odor:** Fruity, Sharp, fragrant (Strong.)

**Taste:** Not available.

**Molecular Weight:** 128.17 g/mole

**Color:** Clear Colorless.

**pH (1% soln/water):** Not available.

**Boiling Point:** 145°C (293°F)

**Melting Point:** -64.6 (-84.3°F)

**Critical Temperature:** 321°C (609.8°F)

**Specific Gravity:** 0.8898 (Water=1)

**Vapor Pressure:** 0.5 kPa (@20°C)

**Vapor Density:** Not available.

**Volatility:** Not available.

**Odor Threshold:** Not available.

**Water/Oil Dist. Coeff.:** The product is more soluble in oil; log(oil/water) = 2.4

**Ionicity (in Water):** Not available.

**Dispersion Properties:** See solubility in water, diethyl ether, acetone.

**Solubility:** Soluble in diethyl ether, acetone. Very slightly soluble in cold water. Practically insoluble in water. Solubility in Water: 0.14 g/100 ml water @ 20 deg. C.; 0.12 g/100 ml water @ 40 deg. C; 2,000 mg/l water @ 23 deg. C

## 10 STABILITY AND REACTIVITY DATA

**Stability:** The product is stable since it is stabilized or inhibited with Hydroquinone monomethyl ether (MEHQ). However, it may undergo explosive polymerization if uninhibited. It may polymerize on exposure to light. Polymerization may occur upon heating. It is stable only if stored and handled under recommended conditions. The stability of the product depends upon the availability of both dissolved oxygen and MEHQ. Inhibitor. The presence of oxygen is necessary for the MEHQ to function effectively. The product should never be stored under an inert gas atmosphere, but it should always be stored under an atmosphere containing 5-21% oxygen by volume. Also, temperatures must be kept low to minimize formation of peroxides and other products. This material is a monomer and may polymerize under certain conditions if the stabilizer / inhibitor is lost. Again, hazardous polymerization may be caused elevated temperature, oxidizers, peroxides, or sunlight.

**Instability Temperature:** Not available.

**Conditions of Instability:** Heat, ignition sources, incompatible materials, light.

**Incompatibility with various substances:** Reactive with oxidizing agent, acids, alkalis. The product may undergo hazardous decomposition, condensation or polymerization.

### DISCLAIMER

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.

**Corrosivity:** Not available.

**Special Remarks on Reactivity:** Incompatible with amines, halogens, peroxides. Sensitive to light.

**Special Remarks on Corrosivity:** Not available.

**Polymerization:** Yes, it may occur under certain conditions. Read special remarks under the section titled "Stability"

## 11 TOXICOLOGICAL INFORMATION

**Routes of Entry:** Absorbed through skin. Dermal contact. Eye contact. Inhalation. Ingestion.

**Toxicity to Animals:** Acute oral toxicity (LD50): 900 mg/kg [Rat]. Acute dermal toxicity (LD50): 1780 mg/kg [Rabbit]. Acute toxicity of the vapor (LC50): 7800 mg/m<sup>3</sup> 2 hours [Mouse]. 3

**Chronic Effects on Humans:** CARCINOGENIC EFFECTS: 3 (Not classifiable for human.) by IARC. May cause damage to the following organs: kidneys, lungs, liver, upper respiratory tract, skin, eyes.

**Other Toxic Effects on Humans:** Hazardous in case of skin contact (sensitizer, permeator), of ingestion, of inhalation (lung irritant). Slightly hazardous in case of skin contact (irritant).

**Special Remarks on Toxicity to Animals:** Lethal Dose/Conc 50% Kill: LD50 [Rabbit] - Route: Skin; Dose: 2 ml/kg

**Special Remarks on other Toxic Effects on Humans:** Acute Potential Health Effects: Cause skin irritation. It can be absorbed through the skin. It may be harmful if absorbed through the skin. Eyes: Causes eye irritation. Inhalation: It causes respiratory tract (nose, throat) irritation causing coughing and wheezing. Inhalation may affect respiration (dyspnea, pulmonary edema, suffocation). Very high exposure may damage the lungs. It may also cause central nervous system effects such as headache, nausea, drowsiness, dizziness, CNS depression. Ingestion: It causes gastrointestinal tract irritation with nausea, vomiting, and diarrhea. It may be harmful if swallowed. It may affect respiration (respiratory stimulation), and behaviour / central nervous system (convulsions, and other symptoms similar to inhalation) Chronic Potential Health Effects: Prolonged or repeated inhalation may affect the liver, kidneys. It may also affect behavior / central nervous system (drowsiness, changes in memory, concentration, or sleeping patterns, and mood (especially irritability and social withdrawal), as well as fatigue and headaches), peripheral and autonomic nervous systems. Prolonged inhalation may effect metabolism (weight loss). Very high exposures may result in pulmonary congestion or damage the lungs. Prolonged or repeated skin contact may cause sensitization an allergic reaction.

## 12 ECOLOGICAL INFORMATION

**Ecotoxicity:** Not available.

**BOD5 and COD:** Not available.

**Products of Biodegradation:** Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

**Toxicity of the Products of Biodegradation:** The products of degradation are less toxic than the product itself.

**Special Remarks on the Products of Biodegradation:** Not available.

## 13 DISPOSAL CONSIDERATIONS

**Waste Disposal:** Waste must be disposed of in accordance with federal, state and local environmental control regulations.

## 14 TRANSPORT INFORMATION

**DOT Classification:** CLASS 3: Flammable liquid.

### DISCLAIMER

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.

**Identification:** Butyl Acrylate, stabilized UNNA: 2348 PG: III

**Special Provisions for Transport:** Not available.

## 15 OTHER REGULATORY INFORMATION

**Federal and State Regulations:** Illinois toxic substances disclosure to employee act: Butyl Acrylate Rhode Island RTK hazardous substances: Butyl Acrylate Pennsylvania RTK: Butyl Acrylate Minnesota: Butyl Acrylate Massachusetts RTK: Butyl Acrylate Massachusetts spill list: Butyl Acrylate New Jersey: Butyl Acrylate New Jersey spill list: Butyl Acrylate California Director's List of Hazardous Substances: Butyl Acrylate TSCA 8 (b) inventory: Butyl Acrylate SARA 313 toxic chemical notification and release reporting: Butyl Acrylate

**Other Regulations:** OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

### Other Classifications:

**WHMIS (Canada):** CLASS B-3: Combustible liquid with a flash point between 37.8°C (100°F). CLASS D-1A: Material causing immediate and serious toxic effects (VERY TOXIC). CLASS D-2B: Material causing other toxic effects (TOXIC). CLASS F: Dangerously reactive material.

### DSCL (EEC):

### HMIS (U.S.A.):

**Health Hazard:** 2

**Fire Hazard:** 3

**Reactivity:** 1

**Personal Protection:** h

### National Fire Protection Association (U.S.A.):

**Health:** 3

**Flammability:** 2

**Reactivity:** 2

**Specific hazard:**

### Protective Equipment:

Gloves, Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Splash goggles.

## 16 Other Information

**References:** Not available.

**Other Special Considerations:** Not available.

**Created:** 10/09/2005 04:27 PM

**Last Updated:** 05/21/2013 12:00 PM

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall RAR Resin & Chemical Industries be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if RAR Resin & Chemical Industries has been advised of the possibility of such damages.